

Sley
Split Air Conditioners









ABOUT US

Hexel Industrial company continues its activities in Ankara Sincan Organized Industrial Zone in a 4000 m2 closed area with the capacity to produce 60000 combi boilers and 3000 boilers annually. Thanks to its wide production range, it can meet all heating needs from 24 kW to 1200 kW. It focuses on a zero-defect approach and 100% customer satisfaction, in line with today's technologies and quality standards, with its high-tech testing and laboratory facilities. It continues to expand its product range by combining consumer demand with superior quality with its growing and developing staff day by day. Customer satisfaction is kept at the highest level with after-sales services, and problems are responded to on-site and quickly with 180 authorized services throughout Türkiye.

In addition to its sales network spread throughout the country, it is taking firm steps towards becoming a reliable brand in the sector with its ever-increasing export potential. Our goal is to become a world brand by adding value to its stakeholders and employees without compromising on high technology and quality. We invite you to be a part of this journey now...



Filter



Airflow









Heating











Reliable Golden Fin





MODEL			SKY 9	SKY 12	SKY 18	SKY 24
Power supply		Ph-V-Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz
Rated Cooling	Capacity	Btu/h	9000(3100~11600)	12000(3800~13400)	18000(6200~21000)	24000(7100~27000)
Cooling Power input		w	800(100~1240)	1320(83~1600)	1550(140~2300)	2600(420~3150)
Cooling Current		A	3.48(0.4~5.4)	5.8(0.8~7.3)	6.7(0.6~10)	11.5(1.8~13.8)
Rated Heating	Capacity	Btu/h	10000(2800~11500)	13000(3700~14200)	19000(4400~23000)	25000(5500~27000)
Heating Power input		w	930(120~1200)	1190(167-1400)	1570(220~2350)	2400(300~2750)
Heating Current		A	4.05(0.5~5.5)	5.3(1.4-6.4)	6.8(0.95-10.2)	11(1.3-12.2)
Seasonal Cooling	Pdesignc	kW	2.6	3.5	5.2	7.0
	SEER	W/W	7.0	6.5	7.4	6.1
	Energy Efficiency Class		A++	A++	A++	A++
Heating(Average)	Pdesignh	kW	2.3	2.8	4.1	4.8
	SCOP	W/W	4.1	4.1	4.0	4.0
	Energy Efficiency Class		A+	A+	A+	A+
	Tbiv	°C	-7	-7	-7	-7
Heating(Warmer)	Pdesignh	kW	2.3	3.0	4.4	5.6
	SCOP	W/W	5.1	5.2	5.1	5.1
	Energy Efficiency Class		A+++	A+++	A+++	A+++
	Tbiv	°C	2	2	2	2
Tol		°C	-15	-15	-15	-15
Max. input consumption		w	2150	2150	2500	3500
Max. current		А	10	10	13	15.5
Starting current		А	/	/	/	/
Indoor air flow (Hi/Mi/Lo)		m3/h	435/333/259	530/430/310	840/680/540	980/817/662
Indoor sound pressure level (Hi/Mi/Lo/Si)		dB(A)	37/32/25/21.5	39.5/35.5/25/21.5	42.5/36/26/20	45/40.5/36/29.5
Indoor sound power level (Hi)		dB(A)	50	54	56	59
Indoor unit	Dimension(W*D*H)	mm	715x194x285	805x194x285	957x213x302	1040x220x327
	Packing (W*D*H)	mm	780x270x365	870x270x365	1035x295x385	1120×405×315
	Net/Gross weight	Kg	6.7/8.8	7.3/9.5	10/13	12.3/15.8
Outdoor sound pressure level		dB(A)	55	55	56	59
Outdoor sound power level		dB(A)	59	64	63	67
Outdoor unit	Dimension(W*D*H)	mm	720x270x495	720x270x495	805×330×554	890x342x673
	Packing (W*D*H)	mm	835x300x540	835x300x540	915x370x615	995x398x740
	Net/Gross weight	Kg	21/22.8	21/22.8	32.7/35.4	42.9/45.9
Refrigerant	Туре		R32	R32	R32	R32
	GWP		675	675	675	675
	Charged quantity	Kg	0.47	0.52	1.08	1.42
Refrigerant piping	Liquid side/ Gas side	mm(inch)	6.35mm(1/4in)/9.52mm(3/8in)	6.35mm(1/4in)/9.52mm(3/8in)	6.35mm(1/4in)/12.7mm(1/2in)	9.52mm(3/8in)/15.9mm(5/8in)
	Max. refrigerant pipe length	m	25	25	30	50
	Max. difference in level	m	10	10	20	25
Connection wiring			1.5x5//	1.5x5//	1.5x5//	2.5x5//
Thermostat type			Remote Control	Remote Control	Remote Control	Remote Control
Operation Indoor(cooling/heating)		°C	17~32/0~30	17~32/0~30	17~32/0~30	17~32/0~30














Hexel Industry and Trade Inc.



- info@hexel.com.tr
- www.hexel.com.tr
- O hexel.kombi



🛇 ASO 2. and 3. OSB Alcı District 2024. Street No:19 Sincan / ANKARA